

Fuse holder terminal blocks for 5 x 20 mm and 5 x 25 mm fuses

Compression clamp

DIN 1 - DIN 3



*Blocks with LED indicator are labeled "+" on the outside of the lever. The indicator can be reversed in the field if required.

** Terminal block with low temperature surfacing :
Storage -60°C
Use -20°C

End stop		th. 9 mm	BADL	V0	0399 903.02
End stop		th. 9,1 mm	BAM	V2	0103 002.26
End stop		th. 9,1 mm	BAM V0	V0	0199 306.03
Rail		35 x 7,5 x 1	PR3.Z2		0174 300.17
Rail		35 x 15 x 2,3	PR4		0168 500.12
Rail		35 x 15 x 1,5	PR5		0168 700.22
Rail		32 x 15 x 1,5	PR1.Z2		0163 050.04


Other end stops, rails and accessories : see section on accessories.

Notes

The use of some accessories may decrease the block's voltage rating. For more information, consult us.

Block matching fuse terminal block M 4/8.SF for line, fuse applications : see section on compression clamp terminal blocks

Type	Part number
M 4/8	0115 523.07




Accessories

	1	End section	grey orange beige		
	2	Test plug			
	3	Comb type jumper bar	35 A		
	4	IDC jumper			
	5	Assembly rod			
	6	Assembly ring			
	7	Fuses 5 x 20 mm	250 V		
		Fuses 5 x 25 mm Fast fusion HPC 1500 A	250 V		
8	Disconnect link bar				
R	See section on markers marking method				

M 4/8.SF...

Spacing 8 mm (.315")



Standard 8 mm block.

Colour	Type	Part numbers
Grey	M 4/8.SF	0115 657.25
Grey **	M 4/8.SF1.TS	0115 658.06
Orange	M 4/8.SF2	0105 135.11
Beige V0	M 4/8.SF.V0	0195 657.26

Characteristics

Wire size	IEC		UL	CSA
	NFC	DIN		
Compression Solid wire	0,5-6 mm ²		22-12 AWG	24-12 AWG
clamp Stranded wire	0,5-4 mm ²		22-12 AWG	24-12 AWG


Voltage		630 V (1)	600 V (1)	250 V
Rated				
Pulse	8 kV			
Pollution degree	3			

Current		6,3 A	10 A	10 A
Rated				

Wire size		4 mm ² / A4	12 AWG	12 AWG
Rated / Gauge				
Wire stripping length	Recomm. screwdriver	Recomm. torque	Protection	
9,5 mm .37"	4 mm .157"	0,5-0,8 Nm 4.4-7.1 lb.in	IP 20 (2) NEMA 1	

M 4/8.SFT

Spacing 8 mm (.315")



M 4/8.SF equipped with two test sockets DIA. 2 mm/.079".

Colour	Type	Part numbers
Grey	M 4/8.SFT	0115 662.22
Beige V0	M 4/8.SFT.V0	0195 662.23

Characteristics

Wire size	IEC		UL	CSA
	NFC	DIN		
Compression Solid wire	0,5-6 mm ²		22-12 AWG	24-12 AWG
clamp Stranded wire	0,5-4 mm ²		22-12 AWG	24-12 AWG

Voltage		400 V (1)	600 V (1)	250 V
Rated				
Pulse	4 kV			
Pollution degree	3			

Current		6,3 A	6,3 A	10 A
Rated				

Wire size		4 mm ² / A4	12 AWG	12 AWG
Rated / Gauge				
Wire stripping length	Recomm. screwdriver	Recomm. torque	Protection	
9,5 mm .37"	4 mm .157"	0,5-0,8 Nm 4.4-7.1 lb.in	IP 20 (2) NEMA 1	

Type	Part numbers	Type	Part numbers
FEM8S V2 th. 1,5 mm	0116 951.15	FEM8S V2 th. 1,5 mm	0116 951.15
FEM8S V2 th. 1,5 mm	0103 923.15	FEM8S V2 th. 1,5 mm	0103 923.15
FEM8S V0 th. 1,5 mm	0196 951.16	FEM8S V0 th. 1,5 mm	0196 951.16
PC81 10 poles	0173 523.11	FC2 DIA. 2 mm	0007 865.26
AD2,5 2 mm	0114 205.20	PC81 10 poles	0173 523.11
TGA8 2 poles	0168 672.11	AD2,5 2 mm	0114 205.20
3 poles	0168 673.12	TGA8 2 poles	0168 672.11
4 poles	0168 674.13	3 poles	0168 673.12
ANT 0168 675.14		4 poles	0168 674.13
FU520 5 x 20		ANT 0168 675.14	
0,5 A	0008 288.15	FU520 5 x 20	
1 A	0008 290.13	0,5 A	0008 288.15
2 A	0008 291.00	1 A	0008 290.13
3,15 A	0008 289.16	2 A	0008 291.00
5 A	0008 292.01	3,15 A	0008 289.16
		5 A	0008 292.01
FU525 5 x 25		FU525 5 x 25	
1,6 A	0167 546.22	0,5 A	0008 288.15
2 A	0167 547.23	1 A	0008 290.13
2,5 A	0167 548.04	2 A	0008 291.00
4 A	0167 549.05	3,15 A	0008 289.16
6,3 A	0167 550.02	5 A	0008 292.01
CN5 0179 371.16		CN5 0179 371.16	

Note : (1) Insulation voltage of terminal block - operating voltage : according to fuse.
(2) Protection index for closed block.