



AM2LED/ASY/500

Mira 2 LED Asymmetric Floodlight - 500W Daylight



Features

Die-cast LED floodlight with textured graphite colour finish

Asymmetric reflector for anti-light pollution

Exceeds the performance of 1000W HQI

Lighting for large open spaces, sports centers and industrial spaces

LED lifespan L70 50,000 hours

Non-dimmable

General Information

Lamp Type	LED
Colour / Finish	Graphite
IP Rating	IP65
IK Rating	IK07
Class Protection	1
Internal / External	External
Surface / Recessed / Suspended	Surface
Warranty (Years)	5
CE Mark	Yes
Width (mm)	655
Height (mm)	645
Depth (mm)	272

Technical Information

Wattage	500W
Lumens Delivered	72862lm
Lm/W	146lm
CRI	70
CCT	5000K
Input	100/270V
Hertz	50/60Hz
Operating Temp	-20 to 50°C

Technical Data - ETIM - Downlight/spot/floodlight (EC001744)

Suitable for surface mounting	Yes
Suitable for built-in mounting	No
Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for ceiling mounting	No
Suitable for traverse mounting	No
Suitable for pedestal/floor mounting	Yes
Suitable for light-track mounting	No
Adjustability	Swivelling
With movement sensor	No
With light sensor	No
Control gear included	Yes
Degree of protection (IP)	IP65
Protection class	I
Max. system power	500 W
Colour of light	White
Colour temperature	5000-5000 K
Colour rendering index CRI	70-79
Rated luminous flux acc. IEC 62722-2-1	72862 lm
Lamp efficacy	146 lm/W
Width	272 mm
Height/depth	645 mm

Datasheet generated from <https://www.electrika.com> last updated Monday, November 4, 2019 1:52:43 PM

