

# Product datasheet

Specifications



## TeSys SK - auxiliary contact block - 1 NO + 1 NC

Local distributor code:

384178548

LA1SK11

EAN Code: 3389110564006

### Main

Range	TeSys
Device short name	LA1SK
Product or component type	Auxiliary contact block
Product compatibility	LC1SK
Auxiliary contacts operation	Instantaneous
Pole contact composition	1 NO + 1 NC
Connections - terminals	Screw clamp terminals 1 cable(s) 1.5...6 mm <sup>2</sup> solid Screw clamp terminals 2 cable(s) 1.5...4 mm <sup>2</sup> solid Screw clamp terminals 1 cable(s) 0.5...6 mm <sup>2</sup> flexible with cable end Screw clamp terminals 2 cable(s) 0.35...2.5 mm <sup>2</sup> flexible with cable end Screw clamp terminals 1 cable(s) 0.35...6 mm <sup>2</sup> flexible without cable end Screw clamp terminals 2 cable(s) 0.35...1.5 mm <sup>2</sup> flexible without cable end

### Complementary

Mounting location	Front side
[Ui] rated insulation voltage	690 V conforming to IEC 60947 690 V conforming to BS 5424 690 V conforming to VDE 0110 group C 690 V conforming to CSA C22.2 No 14
[Ue] rated operational voltage	690 V AC <= 400 Hz
[Ith] conventional free air thermal current	10 A (at 55 °C)
Associated fuse rating	10 A gL conforming to IEC 60947 10 A gL conforming to VDE 0660
Tightening torque	0.8 N.m - on screw clamp terminals
Width	27 mm
Net weight	0.022 kg

### Environment

Standards	CSA C22.2 No 60947-5-1 EN/IEC 60947-5-1 UL 60947-5-1
Product certifications	CB Scheme CE UKCA EAC cULus
IP degree of protection	IP2X
Protective treatment	TC conforming to IEC 60068
Ambient air temperature for operation	-20...50 °C

---

Ambient air temperature for storage	-50...70 °C
Operating altitude	2000 m without derating

---

## Packing Units

---

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.8 cm
Package 1 Width	4.3 cm
Package 1 Length	5.5 cm
Package 1 Weight	28.0 g
Unit Type of Package 2	S01
Number of Units in Package 2	60
Package 2 Height	15.0 cm
Package 2 Width	15.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	1.855 kg

---

## Logistical informations

---

Country of origin	CZ
-------------------	----

---

## Contractual warranty

---

Warranty	18 months
----------	-----------

---

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

#### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	C39a7e5e-6a28-4540-b3bb-b5a727bdce6a
REACH Regulation	<a href="#">REACH Declaration</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>

### Use Again

#### Repack and remanufacture

WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	No