

Auxiliary contact block for TeSys Giga contactor, 1NO + 1NC, side mounting, push-in terminals

LAG8N113

EAN Code: 3606481916310

Main

Range compatibility	TeSys G LC1G	
Range of product	TeSys G	
Range	TeSys	
Device short name	LAG8N	
Product or component type	Auxiliary contact block	
Auxiliary contacts operation	Instantaneous	
Pole contact composition	1 NO + 1 NC	
Connections - terminals	Screw clamp terminals0.752.5 mm²solid stranded without cable end Screw clamp terminals0.752.5 mm²flexible with cable end	

Complementary

Mounting location	Side	
[Ui] rated insulation voltage	600 V conforming to IEC 60947-5-1 600 V - certifications CSA 600 V - certifications UL	
[Ue] rated operational voltage	600 V AC 25400 Hz	
[Ith] conventional free air thermal current	10 A (at 60 °C)	
Irms rated making capacity	140 A AC conforming to IEC 60947-5-1 250 A DC conforming to IEC 60947-5-1	
Permissible short-time rating	100 A 60 °C 1 s 120 A 60 °C 500 ms 140 A 60 °C 100 ms	
Protection type	GG fuse 10 A	
Mechanical durability	8 Mcycles	
Minimum switching current	1 mA	
Minimum switching voltage	17 V	
Non-overlap time	1.5 ms on de-energisation no overlap between NC and NO contact 1.5 ms on energisation no overlap between NC and NO contact	
Insulation resistance	> 10 MOhm	
Height	55.8 mm	
Width	15.4 mm	
Depth	84.8 mm	
Net weight	0.05 kg	

Environment

Standards	EN/IEC 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-5-1 GB 14048.5 IEC 60335-1:Clause 30.2 IEC 60335-2-40:Annex JJ UL 60335-1 UL 60335-2-40:Annex JJ	
Product certifications	CB Scheme CCC cULus CE UKCA	
IP degree of protection	IP20 conforming to IEC 60529	
Protective treatment	тн	
Ambient air temperature for operation	-2560 °C	
Ambient air temperature for storage	-6080 °C	
Operating altitude	3000 m	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.400 cm
Package 1 Width	6.700 cm
Package 1 Length	9.500 cm
Package 1 Weight	59.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	64
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	3.969 kg

Logistical informations

Country of origin CN

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure

Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	6fbdad13-bb7c-47d4-a6d6-d82dd6f54349
REACh Regulation	REACh Declaration
Halogen content performance	Halogen free plastic parts product
PVC free	Yes

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No

Product datasheet

LAG8N113

Installation

Installation Videos

TeSys Giga - How to install the auxiliary contact block