

OTP45BA3M



Products → Low Voltage Products and Systems → Enclosed Switches → Enclosed Switch-Disconnectors

General Information

| | |
|-------------------------------|---|
| Extended Product Type: | OTP45BA3M |
| Product ID: | 1SCA022401R3600 |
| EAN: | 6417019131214 |
| Catalog Description: | OTP45BA3M Enclosed Switch Disconnecter |
| Long Description: | Enclosed Switch Disconnecter, 3-p. 400V AC22 63A, Plastic enclosure, RedYellow Selector handle. Interlocked cover. Defeatable interlocking. |

Ordering

| | |
|--------------------------------|----------|
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85365080 |

Popular Downloads

| | |
|---|-----------------|
| Data Sheet, Technical Information: | 1SCC340009C0201 |
| Instructions and Manuals: | 1SCC340002M0012 |

Dimensions

| | |
|------------------------------------|--------|
| Product Net Width: | 145 mm |
| Product Net Height: | 200 mm |
| Product Net Depth / Length: | 90 mm |
| Product Net Weight: | 0.9 kg |

Technical

| | |
|---|--|
| Rated Operational Current AC-21A (I _e): | (380 ... 415 V) 63 A (500 V) 63 A (690 V) 63 A |
|---|--|

| | |
|---|--------------------------------------|
| Rated Operational Current AC-22A (I _e): | (380 ... 415 V) 63 A (690 V) 63 A |
|---|--------------------------------------|

| | |
|---|--------------------------------------|
| Rated Operational Current AC-23A (I _e): | (380 ... 415 V) 45 A (690 V) 20 A |
|---|--------------------------------------|

| | |
|---|---------------------|
| Conventional Thermal Current (I _{the}): | Fully Enclosed 63 A |
|---|---------------------|

| | |
|--|------|
| Rated Impulse Withstand Voltage (U _{imp}): | 1 kV |
|--|------|

| | |
|--|------------------------------|
| Rated Insulation Voltage (U_i): | acc. to IEC/EN 60664-1 750 V |
|--|------------------------------|

| | |
|-----------------------------------|--------------------|
| Rated Operational Voltage: | Main Circuit 750 V |
|-----------------------------------|--------------------|

| | |
|--|-------------------|
| Rated Short-Circuit Making Capacity (I_{cm}): | (690 V AC) 1.4 kA |
|--|-------------------|

| | |
|--|--|
| Rated Short-time Withstand Current (I_{cw}): | for 1 s 1 kA |
| Power Loss: | at Rated Operating Conditions per Pole 1.5 W |
| Pollution Degree: | 3 |
| Handle Color: | Red / Yellow |
| Handle Type: | Selector handle |
| Position of Line Terminals: | Top In - Bottom Out |
| Standards: | IEC 60947-1, -3 |
| Number of Poles: | 3 |
| Cable Cross-Section: | 25 mm ² |
| Cable Entry Position: | Up/Down |
| Cable Outlets Per Side: | 2xM32+M16 / 2xM32+M16 |
| Degree of Protection: | acc. to IEC 60529 IP65 |
| Enclosure Material: | Plastic |
| Maximum Mounted Auxiliary Contacts: | 2 NO, 2 NC |
| Position of Neutral Terminals: | Top In - Bottom Out |
| Position of PE Terminals: | Top In - Bottom Out |

Environmental

| | |
|-----------------------------------|-----------------------------------|
| RoHS Status: | Following EU Directive 2011/65/EU |
| Environmental Information: | 1SCC340034D0202 |

Certificates and Declarations (Document Number)

| | |
|--|-----------------|
| BV Certificate: | 1SCC340018D0204 |
| Declaration of Conformity - CE: | 1SCC340003D2704 |
| DNV Certificate: | 1SCC340045D0203 |
| DNV GL Certificate: | 1SCC340045D0203 |
| Environmental Information: | 1SCC340034D0202 |
| GL Certificate: | 1SCC301042D0201 |
| Instructions and Manuals: | 1SCC340002M0012 |
| RoHS Information: | 1SCC340034D0202 |

Container Information

| | |
|--|---------|
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 148 mm |
| Package Level 1 Depth / Length: | 162 mm |
| Package Level 1 Height: | 222 mm |
| Package Level 1 Gross Weight: | 1 kg |

Package Level 1 EAN:

6417019131214

Classifications

Object Classification Code:

Q

ETIM 5:

EC000216 - Switch disconnecter

ETIM 6:

EC000216 - Switch disconnecter

ETIM 7:

EC000216 - Switch disconnecter

