

ZA2BD2

black selector switch - 2 positions - standard handle



Main

| | |
|---------------------------|-----------------|
| Range of product | Harmony XAC |
| Product or component type | Selector switch |
| Component name | ZA2 |
| Product compatibility | XACA |

Complementary

| | |
|-------------------------------|---|
| Marking | Unmarked |
| Cap/operator or lens colour | Black |
| Mounting location | Front of enclosure Base of enclosure |
| Sale per indivisible quantity | 1 |
| Product weight | 0.018 kg |

Environment

| | |
|---------------------------------------|--|
| standards | EN/IEC 60204-32 EN/IEC 60947-5-1 UL 508 CSA C22.2 No 14 |
| ambient air temperature for operation | -25...70 °C |
| ambient air temperature for storage | -40...70 °C |
| vibration resistance | 15 gn (f = 10...500 Hz) conforming to IEC 60068-2-6 |
| shock resistance | 100 gn conforming to IEC 60068-2-27 |
| overvoltage category | Class II conforming to IEC 61140 |
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to EN 50102 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.